

INDUSTRIAL HEATING



Environment-Friendly Electric Heaters

Exceed NEMA 3R Standards 75kW and 150kW Weatherproof Models



- Clean, electric heat free from the moisture and fumes associated with other types of heating
- Rugged, weatherproof enclosures for reliable operation outdoors
- Operates at extremely low noise levels
- Forklift pockets and removable casters for easy lifting and placement at the job site
- 3-HP blower with variable speed drive for precise air flow control
- User-friendly NEMA 4 control panel with main disconnect, high limit controller and an industrial three-pole shutdown contactor for each heating circuit
- Emergency shutdown button plus indicator lamps for Power On, Heat On, Low Air Flow and Over Temperature

* Process controller with remote setpoint capacity, digital communications and 4-20 mA analog output

| Capacity | Max BTU | Max Outlet Temperature | Max Air Flow | Voltage | AMP Rating | Overall Dimensions (L x W x H) | Weight |
|----------|---------|------------------------|--------------|--------------|------------|--------------------------------|----------|
| 75 kW | 256,000 | 300° F | 5000 CFM | 480V 3-phase | 92 | 6'4" x 2'9" x 6'6" | 1948 lbs |
| 150 kW | 512,000 | 300° F | 5000 CFM | 480V 3-phase | 190 | 6'4" x 2'9" x 6'6" | 1948 lbs |

ON SITE MANUFACTURING, INC.

3636 West Frontage Road Austin, Indiana 47102-8824

www.onsitemfg.com

866-935-6764

sales@onsitemfg.com