

INDUSTRIAL HEATING

Environment-Friendly
Electric Heaters

Exceed NEMA 3R Standards

75kW & 150 kW Weatherproof
Models



Capacity	Max BTU	Max Outlet Temperature	Max Air Flow	Voltage	AMP Rating	Overall Dimensions (LxWxH)	Weight
75kW	256,000	300° F	5000 CFM 3" Static Pressure	480V 3-Phase	92	6'10"x2'9"x4'8"	1480 lbs
150kW	512,000	300° F	5000 CFM 3" Static Pressure	480V 3-Phase	190	6'10"x2'9"x4'8"	1480 lbs

- Fits through standard doorway and is stackable
- Clean electric heat free from the moisture and fumes associated with other types of heating
- Rugged weatherproof enclosures for reliable operation outdoors
- Operates at extremely low noise levels
- 3-way forklift pockets, lifting eyes and removable casters for easy lifting and placement at the job site
- 3-HP blower with variable speed drive for precise air flow control
- Horizontal hot air discharge
- User-friendly NEMA 4 control panel with main disconnect, high limit controller and an industrial three-pole shutdown contactor for each heating circuit
- Emergency shutdown button plus indicator lamps for Power On, Heat On, Low Air Flow and Over Temperature
- Process controller with remote setpoint capacity, digital communications and 4-20 mA analog output

ON SITE MANUFACTURING, INC.

www.onsitemfg.com ▲
Toll Free: 866-935-6764



▲ sales@onsitemfg.com
FAX: 812-794-6042