



# COMPACT INDUSTRIAL HEATER

## 65 kW

*Environment-Friendly  
Electric Heater*

- Exceeds NEMA 3R standards
- Fits through standard doorway
- Rugged weather resistant enclosures for reliable operation outdoors
- Forklift pockets and removable casters for easy lifting and placement at the job site
- Operates at extremely low noise levels with major components vibration isolated
- Effective for use in Food Processing Plants, Warehouses, Pallet Manufacturing, or any large facility requiring dry, high temperature heat
- Free from moisture and fumes associated with other heating types
- Two (2) stages of heat with hybrid solid state relay for precise temperature control
- Horizontal hot air discharge allows use of duct work, or heater can be placed directly into space
- Emergency shutdown button plus indicator lamps for Power On, Heat On, Low Air Flow and Over Temperature
- Industrial direct digital controller with the option to control space, return air or discharge air temperature with a 0-10 VDC analog output

Capacity	Maximum Output (BTU/Hr)	Maximum Temperature Outlet	Maximum Air Flow (CFM)	Voltage	AMP Rating	Overall Dimensions (L x W x H)	Weight (lbs)
65 kW	222,000	300° F	2,600	480V 3 Phase	92	70" x 29" x 44"	740



www.HeaterSales.com  
 www. OnSiteMfg.com  
 sales@onsitemfg.com  
 Toll Free: 866.935.6764