



COMPACT INDUSTRIAL AIR HANDLER

5,000 CFM Air Handler
 250,000 BTU / HR (20 Tons, Cooling)
 600,000 BTU / HR (Hot Water Heat)
 384,000 BTU / HR (Steam)*

Design Specifications

- Fits through a standard doorway
- Variable speed drive on fan to control air flow
- Very quiet at any fan speed
- 3-way fork lift pockets and removable casters for easy placement
- Water coil approved to 250 PSI
- Steam coil approved to 75 PSI
- One or two 20" discharge ducts available - diffuser or custom outlet connections available

Chilled Water Cooling Specifications

- Condensate pump with alarm (pump @ 19' of head)
- Works with customer's chilled water or a temporary chiller

Hot Water Heat Specifications

- Works with customer's hot water system or temporary hot water boiler @ approximately 200° F
- Produces over 100° F temperature delta on the air side

* STEAM: 4500 CFM, SPSI +55° outside air, operating pressure 0 - 25 psi, maximum temperature 225°

Water Connection	Power Requirements	Power Connection	Air Flow (CFM)	Dimensions (L x W x H)	Weight (lbs)	Discharge Duct Diameter
1.5" Victaulic	480 V 3 PH / 10 AMP	Leviton CS-81-65C (male on AH)	5,000	67" x 32" x 52"	1,130	20"



www.HeaterSales.com
 www.OnSiteMfg.com
 sales@onsitemfg.com
 Toll Free: 866.935.6764