

# COMPACT INDUSTRIAL HEATER

## 75/150 kW

*Environment-Friendly  
Electric Heater*



- Clean electric heat, free from the moisture and fumes associated with other types of heating
- Fits through a standard doorway
- Rugged weather resistant enclosures for reliable operation outdoors
- Operates at extremely low noise levels with major components vibration isolated
- Forklift pockets, lifting eyes and removable casters for easy lifting, stackability and placement at the job site
- Exceed NEMA 3R Standards
- Horizontal in-line hot air discharge
- Eight (8) stages of heat with hybrid solid state relay control
- Emergency shutdown button plus indicator lamps for Power On, Heat On, Low Air Flow and Over Temperature
- Industrial direct digital controller with the option to control space, return air or discharge air temperature with a 0-10 VD analog output

Capacity	Maximum BTU	Maximum Outlet Temperature	Maximum Air Flow	Voltage	AMP Rating	Overall Dimensions (L x W x H)	Weight (lbs)
75 kW	256,000	300° F	3,200 CFM 1 ½" Static Pressure	480V 3 Phase	92	81" x 33" x 56"	1,160
150 kW	512,000		4,400 CFM 3" Static Pressure		190		



www.HeaterSales.com  
www. OnSiteMfg.com  
sales@onsitemfg.com  
Toll Free: 866.935.6764